

# **OCV/OCR Vision Inspection System**











OCR / OCV - 12 LINES

TYPES OF INSPECTION

Camera Support

VARIOUS Statutory MIS REPORTS

### FEATURES

- 15" Touch screen with user-friendly multilingual user interface
- High resolution smart camera-based system with optics and state of the art customized illumination
- Inspection type:

OCR / OCV: Upto 12 lines with 20 characters in each line - 1D Code: All types of barcodes with 2 inspection zones - 2D Code: 2D code inspection with verification

- Pharmacode: Color / black & white Pharmacode scanning with value match
- Presence / absence: 2 zones of presence / absence inspection
  - High speed industrial computer-based inspection system with multiple camera connection option Optional: Variable data inspection

#### **FEATURES**

- Tracking of product which ensures foolproof rejection
  System backup & restore facility
- Flexibility to choose as per application and machine requirement
- Rejection unit-air nozzle / pusher based
- Rejection verification sensor
- Rejection bin with rejection bin full sensor
- 'Machine Stop' signal to stop the Packaging Machine
- No-label detection system
  - Various statutory reports like audit trial, product / batch wise non-editable Reports / 4 User levels & role management - Administrator, Supervisor, Operator & QA Meets 21 CFR Part 11 & GAMP compliance

Versions	Smart Camera		PC BASED
Resolution	1280 x1024 Pixels	1280 x 1024 Pixels	2560 x 2560 Pixels
Area covered	60 X 45 mm	90 X 72 mm	120 x 120 mm
Font size (minimum)	1.8 mm	1.8 mm	1.2 mm
Focal length	12 mm	12 mm	12 mm
Max. speed (Standard Inspection)	300 Scans/min	300 Scans/min	300 Scans/min

#### SYSTEM SPECIFICATIONS



## **Sirius Vision**